

OFFICIAL QUOTE

225KVA 575 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER





225KVA 575 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER


\$6,550.00 CAD


Three Phase Autotransformer with a capacity of 225kVA, transforming 575Y Volts to 380Y Volts

SKU: RA225J1-F

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 575Y Volts to 380Y Volts



OFFICIAL QUOTE



225KVA 575 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	492 lbs
Phases	<u>3</u>
kVA	225
Connection	3PhA-NT-1
Primary Voltage	<u>575</u>
Primary Max Current	225.9A
Primary Markings	H1-H2-H3
Primary Terminals	600MCM-2
Secondary Voltage	380
Secondary Max Current	<u>341.9A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-7</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

225KVA 575 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------