



**150KVA 380 VOLTS TO 416 VOLTS  
SINGLE PHASE AUTOTRANSFORMER**



**150KVA 380 VOLTS TO 416  
VOLTS SINGLE PHASE  
AUTOTRANSFORMER**

**\$2,419.80 CAD**

Single Phase Autotransformer with a capacity of 150kVA, transforming 380 Volts to 416 Volts

**SKU:** MC150F-G

**Categories:** [Autotransformer](#)

## SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 150kVA, transforming 380 Volts to 416 Volts



## PRODUCT SPECIFICATIONS

Weight	161.5 lbs
Phases	<a href="#">1</a>
kVA	<a href="#">150</a>
Connection	<a href="#">1PhA-NT-1</a>
Primary Voltage	<a href="#">380</a>
Primary Max Current	<a href="#">227.9A</a>
Primary Markings	<a href="#">X0-X1</a>
Primary Terminals	<a href="#">600MCM-2</a>
Secondary Voltage	<a href="#">416</a>
Secondary Max Current	<a href="#">208.2A</a>
Secondary Markings	<a href="#">H0-H1</a>
Secondary Terminals	<a href="#">600MCM-2</a>
Primary Taps	<a href="#">N/A</a>
Conductor Material	<a href="#">Copper</a>
Insulation Class	<a href="#">220°C (Class H)</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">0.5 – 1.5%</a>
Sound (db)	<a href="#">45 dB</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-4</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>



OFFICIAL QUOTE

150KVA 380 VOLTS TO 416 VOLTS  
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	<a href="#">Canada/RPM</a>
----------------------	----------------------------