

#### **OFFICIAL QUOTE**

### 225KVA 550 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER





### 225KVA 550 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER


\$10,600.20 CAD


Three Phase Autotransformer with a capacity of 225kVA, transforming 550Y Volts to 208Y Volts

**SKU:** RA225J2-B

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 550Y Volts to 208Y Volts



### **OFFICIAL QUOTE**



## 225KVA 550 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER

### **PRODUCT SPECIFICATIONS**

Weight	988 lbs
Phases	<u>3</u>
kVA	225
Connection	<u>3PhA-NT-1</u>
Primary Voltage	<u>550</u>
Primary Max Current	236.2A
Primary Markings	H1-H2-H3
Primary Terminals	600MCM-2
Secondary Voltage	208
Secondary Max Current	624.5A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 - 4.5%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 225KVA 550 VOLTS TO 208 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------