

OFFICIAL QUOTE

45KVA 110 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER





45KVA 110 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER

\$4,551.40 CAD


Three Phase Autotransformer with a capacity of 45kVA, transforming 110Y Volts to 380Y Volts

SKU: RC45A2-F

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 45kVA, transforming 110Y Volts to 380Y Volts



OFFICIAL QUOTE



45KVA 110 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 241 lbs |
| Phases | <u>3</u> |
| kVA | 45 |
| Connection | <u>3PhA-NT-1</u> |
| Primary Voltage | 110 |
| Primary Max Current | 236.2A |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | 600MCM-2 |
| Secondary Voltage | 380 |
| Secondary Max Current | 68.4A |
| Secondary Markings | H1-H2-H3 |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>2.5 – 4.5%</u> |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

45KVA 110 VOLTS TO 380 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | <u>Canada/RPM</u> |
|----------------------|-------------------|
|----------------------|-------------------|