



150KVA 347 VOLTS TO 550 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$6,614.80 CAD

Single Phase Autotransformer with a capacity of 150kVA, transforming 347 Volts to 550 Volts

SKU: MC150E-J2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 150kVA, transforming 347 Volts to 550 Volts



PRODUCT SPECIFICATIONS

Weight	463.8 lbs
Phases	1
kVA	150
Connection	1PhA-NT-1
Primary Voltage	347
Primary Max Current	249.6A
Primary Markings	X0-X1
Primary Terminals	600MCM-2
Secondary Voltage	550
Secondary Max Current	157.5A
Secondary Markings	H0-H1
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 347 VOLTS TO 550 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------