

OFFICIAL QUOTE

200KVA 440 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER





200KVA 440 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$10,194.80 CAD

Single Phase Autotransformer with a capacity of 200kVA, transforming 440 Volts to 230 Volts

SKU: MC200H2-C1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 200kVA, transforming 440 Volts to 230 Volts



OFFICIAL QUOTE

200KVA 440 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	757.2 lbs
Phases	1
kVA	200
Connection	1PhA-NT-1
Primary Voltage	440
Primary Max Current	262.4A
Primary Markings	<u>H0-H1</u>
Primary Terminals	600MCM-2
Secondary Voltage	230
Secondary Max Current	502A
Secondary Markings	<u>X0-X1</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8S
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

200KVA 440 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------