



**112KVA 240 VOLTS TO 208 VOLTS
THREE PHASE AUTOTRANSFORMER**



**112KVA 240 VOLTS TO 208
VOLTS THREE PHASE
AUTOTRANSFORMER**

\$3,386.90 CAD

Three Phase Autotransformer with a capacity of 112.5kVA, transforming 240Y Volts to 208Y Volts

SKU: RC112C-B

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 112.5kVA, transforming 240Y Volts to 208Y Volts



PRODUCT SPECIFICATIONS

Weight	121 lbs
Phases	3
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	240
Primary Max Current	270.6A
Primary Markings	H1-H2-H3
Primary Terminals	600MCM-2
Secondary Voltage	208
Secondary Max Current	312.3A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

112KVA 240 VOLTS TO 208 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------