



75KVA 230 VOLTS TO 240/480 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$5,011.23 CAD

Single Phase Isolation Transformer with a capacity of 75kVA, transforming 230 Volts to 240/480 Volts

SKU: SA75C1-L/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 75kVA, transforming 230 Volts to 240/480 Volts

75KVA 230 VOLTS TO 240/480 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



PRODUCT SPECIFICATIONS

Weight	405 lbs
Phases	1
kVA	75
Connection	1Ph-2coil-5T-SU
Primary Voltage	230
Primary Max Current	326.09A
Primary Markings	X1-X2
Primary Terminals	Pads
Secondary Voltage	240/480
Secondary Max Current	312.5A
Secondary Markings	H1-H2
Secondary Terminals	Pads
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.50% (DOE 2016/NRCan 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	50
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



OFFICIAL QUOTE

75KVA 230 VOLTS TO 240/480 VOLTS
SINGLE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey