



75KVA 120 VOLTS TO 208 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$4,409.40 CAD

Single Phase Autotransformer with a capacity of 75kVA, transforming 120 Volts to 208 Volts

SKU: MC75A-B

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 75kVA, transforming 120 Volts to 208 Volts



PRODUCT SPECIFICATIONS

Weight	284 lbs
Phases	1
kVA	75
Connection	1PhA-NT-1
Primary Voltage	120
Primary Max Current	360.8A
Primary Markings	X0-X1
Primary Terminals	Pads
Secondary Voltage	208
Secondary Max Current	208.2A
Secondary Markings	H0-H1
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 120 VOLTS TO 208 VOLTS

SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------