


OFFICIAL QUOTE

2500KVA 400 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER





2500KVA 400 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER


\$34,557.60 CAD


Three Phase Autotransformer with a capacity of 2500kVA, transforming 400Y Volts to 480Y Volts

SKU: RA2500G1-H

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 2500kVA, transforming 400Y Volts to 480Y Volts



OFFICIAL QUOTE

2500KVA 400 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 2660 lbs |
|----------------------------|---|
| Phases | <u>3</u> |
| kVA | 2500 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 400 |
| Primary Max Current | 3608.4A |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 480 |
| Secondary Max Current | 3007A |
| Secondary Markings | H1-H2-H3 |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 0.5 - 1.5% |
| Sound (db) | 60 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | E3R-10 |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

2500KVA 400 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|