

OFFICIAL QUOTE

15VA 400 VOLTS TO 115 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





15VA 400 VOLTS TO 115 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

\$2,623.15 CAD

Single Phase Isolation Transformer with a capacity of 15kVA, transforming 400 Volts to 115 Volts

SKU: SC15G1-A1/Z3 Categories: Isolation Transformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Isolation Transformer with a capacity of 15kVA, transforming 400 Volts to 115 Volts



OFFICIAL QUOTE

15VA 400 VOLTS TO 115 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 215 lbs |
|----------------------------|---|
| Phases | 1 |
| kVA | <u>15</u> |
| Connection | 1Ph-2coil-5t-SD |
| Primary Voltage | 400 |
| Primary Max Current | <u>37.5A</u> |
| Primary Markings | <u>H1-H2</u> |
| Primary Terminals | <u>#2-14 AWG</u> |
| Secondary Voltage | 115 |
| Secondary Max Current | <u>130.43A</u> |
| Secondary Markings | <u>X1-X2</u> |
| Secondary Terminals | <u>#2-14 AWG</u> |
| Primary Taps | <u>+/-2 x 2.5%</u> |
| Conductor Material | Copper |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | 97.70% (DOE 2016/NRCan 2019) |
| Impedance Range | <u>4.0 - 6.0%</u> |
| Sound (db) | <u>45</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-4</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise | <u>150°C</u> |

The quote is valid 30 days from 24 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



OFFICIAL QUOTE

15VA 400 VOLTS TO 115 VOLTS SINGLE PHASE ISOLATION TRANSFORMER



| Insuation Class | <u>150°C</u> |
|----------------------|--|
| Country/Manufacturer | Canada/RPM |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |