


OFFICIAL QUOTE

37.5KVA 575 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER





37.5KVA 575 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$2,497.44 USD

Single Phase Autotransformer with a capacity of 37.5kVA, transforming 575 Volts to 230 Volts

SKU: MC37J1-C1

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 37.5kVA, transforming 575 Volts to 230 Volts



OFFICIAL QUOTE





PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 212.6 lbs |
| Phases | 1 |
| kVA | <u>37.5</u> |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | <u>575</u> |
| Primary Max Current | 37.7A |
| Primary Markings | H0-H1 |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 230 |
| Secondary Max Current | 94.1A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | #2/0-6 AWG |
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>1.5 - 3.5%</u> |
| Sound (db) | 45 dB |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

37.5KVA 575 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|