


OFFICIAL QUOTE

75KVA 110 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER





75KVA 110 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$6,862.60 CAD

Single Phase Autotransformer with a capacity of 75kVA, transforming 110 Volts to 480 Volts

SKU: MC75A2-H Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 75kVA, transforming 110 Volts to 480 Volts



OFFICIAL QUOTE

75KVA 110 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| Weight | 470 lbs |
|----------------------------|---|
| Phases | 1 |
| kVA | 75 |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | <u>110</u> |
| Primary Max Current | <u>393.6A</u> |
| Primary Markings | <u>X0-X1</u> |
| Primary Terminals | Pads |
| Secondary Voltage | <u>480</u> |
| Secondary Max Current | <u>90.2A</u> |
| Secondary Markings | <u>H0-H1</u> |
| Secondary Terminals | <u>#2/0-6 AWG</u> |
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Insulation Class | <u>220°C (Class H)</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | <u>N/A</u> |
| Impedance Range | <u>2.5 - 4.5%</u> |
| Sound (db) | <u>55 dB</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-7</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | <u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u> <u>Registered</u> |

The quote is valid 30 days from 20 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



OFFICIAL QUOTE

75KVA 110 VOLTS TO 480 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM