


OFFICIAL QUOTE

3KVA 415 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER





3KVA 415 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$779.90 CAD

Single Phase Autotransformer with a capacity of 3kVA, transforming 415 Volts to 230 Volts

SKU: MC3G2-C1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 3kVA, transforming 415 Volts to 230 Volts



OFFICIAL QUOTE



3KVA 415 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 56.5 lbs |
| Phases | 1 |
| kVA | <u>3</u> |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | 415 |
| Primary Max Current | <u>4.2A</u> |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | Terminal Blocks |
| Secondary Voltage | 230 |
| Secondary Max Current | <u>7.5A</u> |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | Terminal Blocks |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 180°C (Class F) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.5 - 3.5% |
| Sound (db) | <u>40 dB</u> |
| Enclosure Type | NEMA 1 |
| Enclosure Size | <u>E1-0</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

3KVA 415 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|