



30KVA 415 VOLTS TO 415Y/240 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$3,218.02 USD

Three Phase Isolation Transformer with a capacity of 30kVA, transforming 415 Volts to 415Y/240 Volts

SKU: BA30G2-N2/Z3

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Isolation Transformer with a capacity of 30kVA, transforming 415 Volts to 415Y/240 Volts



PRODUCT SPECIFICATIONS

Weight	298 lbs
Phases	3
kVA	30
Connection	3Ph-DY-5T-SU
Primary Voltage	415
Primary Max Current	41.74A
Primary Markings	H1-H2-H3
Primary Terminals	#2-14 AWG
Secondary Voltage	415Y/240
Secondary Max Current	41.74A
Secondary Markings	X0-X1-X2-X3
Secondary Terminals	#2-14 AWG
Primary Taps	+/- 2 x 2.5%
Conductor Material	Aluminum
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.23% (DOE 2016/NRCAN 2019)
Impedance Range	4.0 – 6.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperature Rise	150°C



OFFICIAL QUOTE

30KVA 415 VOLTS TO 415Y/240
VOLTS THREE PHASE ISOLATION
TRANSFORMER



Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey