

#### **OFFICIAL QUOTE**

## 150KVA 208 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER





### 150KVA 208 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER


\$11,491.20 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 208Y Volts to 550Y Volts

**SKU:** RC150B-J2

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 208Y Volts to 550Y Volts



### **OFFICIAL QUOTE**



# 150KVA 208 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	826 lbs
Phases	<u>3</u>
kVA	<u>150</u>
Connection	3PhA-NT-1
Primary Voltage	208
Primary Max Current	416.4A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>550</u>
Secondary Max Current	<u>157.5A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>2.5 – 4.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 150KVA 208 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------