

#### **OFFICIAL QUOTE**

## 45KVA 600 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER





# 45KVA 600 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

\$6,860.53 CAD


Three Phase Isolation Transformer with a capacity of 45kVA, transforming 600 Volts to 220Y/127 Volts

**SKU:** BC45J-S2/Z3

**Categories:** <u>Isolation Transformers</u>

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Isolation Transformer with a capacity of 45kVA, transforming 600 Volts to 220Y/127 Volts



### **OFFICIAL QUOTE**



## 45KVA 600 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

## **PRODUCT SPECIFICATIONS**

| PRODUCT SPECIFICATIONS     |                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------|
| Weight                     | 397 lbs                                                                              |
| Phases                     | 3                                                                                    |
| kVA                        | 45                                                                                   |
| Connection                 | 3Ph-DY-5T-SD                                                                         |
| Primary Voltage            | 600                                                                                  |
| Primary Max Current        | 43.3A                                                                                |
| Primary Markings           | H1-H2-H3                                                                             |
| Primary Terminals          | #2-14 AWG                                                                            |
| Secondary Voltage          | 220Y/127                                                                             |
| Secondary Max Current      | 118.09A                                                                              |
| Secondary Markings         | <u>X0-X1-X2-X3</u>                                                                   |
| Secondary Terminals        | #2-14 AWG                                                                            |
| Primary Taps               | +/- 2 x 2.5%                                                                         |
| Conductor Material         | Copper                                                                               |
| BIL (Insulation) Level     | 10kV                                                                                 |
| Efficiency (@35% Load) %   | 98.40% (DOE 2016/NRCan 2019)                                                         |
| Impedance Range            | 4.0 - 6.0%                                                                           |
| Sound (db)                 | 45                                                                                   |
| Enclosure Type             | NEMA 3R Indoor                                                                       |
| Enclosure Size             | <u>E3R-6</u>                                                                         |
| Finish/Colour              | Polyester Powder Coat - ANSI/ASA 61 Grey                                             |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Temperatue Rise            | 150°C                                                                                |



### **OFFICIAL QUOTE**



## 45KVA 600 VOLTS TO 220Y/127 VOLTS THREE PHASE ISOLATION TRANSFORMER

| Insuation Class      | 150°C                                    |
|----------------------|------------------------------------------|
| Country/Manufacturer | Canada/RPM                               |
| Finish/Colour        | Polyester Powder Coat - ANSI/ASA 61 Grey |