

### **OFFICIAL QUOTE**

## 30KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





### 30KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$2,574.30 CAD

Three Phase Autotransformer with a capacity of 30kVA, transforming 277Y Volts to 575Y Volts

SKU: RC30D-J1

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 30kVA, transforming 277Y Volts to 575Y Volts



### **OFFICIAL QUOTE**

# 575 VOLTS ANSFORMER

## 30KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER

### **PRODUCT SPECIFICATIONS**

Weight	127 lbs
Phases	3
kVA	30
Connection	<u>3PhA-NT-1</u>
Primary Voltage	120/240
Primary Max Current	62.5A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	#2-14 AWG
Secondary Voltage	575
Secondary Max Current	30.1A
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-5</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

## 30KVA 277 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------