

#### **OFFICIAL QUOTE**

## 45KVA 415 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER





# 45KVA 415 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER

\$1,537.10 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 415Y Volts to 440Y Volts

**SKU:** RC45G2-H2

**Categories:** Autotransformer

#### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Three Phase Autotransformer with a capacity of 45kVA, transforming 415Y Volts to 440Y Volts



## **OFFICIAL QUOTE**



## 45KVA 415 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	20 lbs
Phases	<u>3</u>
kVA	<u>45</u>
Connection	3PhA-NT-1
Primary Voltage	415
Primary Max Current	62.6A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	#2-14 AWG
Secondary Voltage	440
Secondary Max Current	<u>59A</u>
Secondary Markings	H1-H2-H3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	180°C (Class F)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 - 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-1</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



## **OFFICIAL QUOTE**

# 45KVA 415 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------