

OFFICIAL QUOTE

225KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER





225KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER

\$13,305.60 CAD

Three Phase Autotransformer with a capacity of 225kVA, transforming 208Y Volts to 400Y Volts

SKU: RC225B-G1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 208Y Volts to 400Y Volts



OFFICIAL QUOTE



225KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	979 lbs
Phases	<u>3</u>
kVA	<u>225</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	208
Primary Max Current	624.5A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	400
Secondary Max Current	<u>324.8A</u>
Secondary Markings	H1-H2-H3
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-8</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

225KVA 208 VOLTS TO 400 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM