


OFFICIAL QUOTE

500KVA 440 VOLTS TO 110 VOLTS THREE PHASE AUTOTRANSFORMER





500KVA 440 VOLTS TO 110 VOLTS THREE PHASE AUTOTRANSFORMER


\$18,920.29 USD


Three Phase Autotransformer with a capacity of 500kVA, transforming 440Y Volts to 110Y Volts

SKU: RA500H2-A2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 500kVA, transforming 440Y Volts to 110Y Volts



OFFICIAL QUOTE



500KVA 440 VOLTS TO 110 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 2357 lbs |
| Phases | <u>3</u> |
| kVA | 500 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 440 |
| Primary Max Current | 656.1A |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 110 |
| Secondary Max Current | <u>2624.3A</u> |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Aluminum |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>2.5 – 4.5%</u> |
| Sound (db) | 60 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-10</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

500KVA 440 VOLTS TO 110 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|