

OFFICIAL QUOTE

500KVA 440 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER





500KVA 440 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER


\$17,870.30 CAD

Three Phase Autotransformer with a capacity of 500kVA, transforming 440Y Volts to 230Y Volts

SKU: RA500H2-C1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 500kVA, transforming 440Y Volts to 230Y Volts



OFFICIAL QUOTE



500KVA 440 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	1660 lbs
Phases	3
kVA	500
Connection	<u>3PhA-NT-1</u>
Primary Voltage	440
Primary Max Current	656.1A
Primary Markings	H1-H2-H3
Primary Terminals	<u>Pads</u>
Secondary Voltage	230
Secondary Max Current	1255.1A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	<u>Aluminum</u>
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	60
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

500KVA 440 VOLTS TO 230 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------