

#### **OFFICIAL QUOTE**

## 500KVA 415 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





### 500KVA 415 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$11,595.30 CAD

Three Phase Autotransformer with a capacity of 500kVA, transforming 415Y Volts to 575Y Volts

SKU: RA500G2-J1

**Categories:** Autotransformer

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 500kVA, transforming 415Y Volts to 575Y Volts



### **OFFICIAL QUOTE**





### **PRODUCT SPECIFICATIONS**

Marinda	000 lb c
Weight	982 lbs
Phases	3
kVA	<u>500</u>
Connection	3PhA-NT-1
Primary Voltage	415
Primary Max Current	695.6A
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	<u>575</u>
Secondary Max Current	502A
Secondary Markings	H1-H2-H3
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	<u>Aluminum</u>
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 - 3.0%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



### **OFFICIAL QUOTE**

# 500KVA 415 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------