


OFFICIAL QUOTE

75KVA 480 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER





75KVA 480 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$6,862.60 CAD

Single Phase Autotransformer with a capacity of 75kVA, transforming 480 Volts to 110 Volts

SKU: MC75H-A2

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 75kVA, transforming 480 Volts to 110 Volts



OFFICIAL QUOTE



75KVA 480 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| Weight | 470 lbs |
|----------------------------|--------------------------------------------------------------------------------------|
| Phases | 1 |
| kVA | <u>75</u> |
| Connection | 1PhA-NT-1 |
| Primary Voltage | 480 |
| Primary Max Current | 90.2A |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | #2/0-6 AWG |
| Secondary Voltage | 110 |
| Secondary Max Current | 393.6A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 2.5 - 4.5% |
| Sound (db) | <u>55 dB</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-7</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

75KVA 480 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|