


OFFICIAL QUOTE

75KVA 460 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER





75KVA 460 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$3,683.51 USD


Single Phase Autotransformer with a capacity of 75kVA, transforming 460 Volts to 230 Volts

SKU: MC75H1-C1

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 75kVA, transforming 460 Volts to 230 Volts



OFFICIAL QUOTE





PRODUCT SPECIFICATIONS

Matuka	205.1 lb.
Weight	325.1 lbs
Phases	1
kVA	<u>75</u>
Connection	<u>1PhA-NT-1</u>
Primary Voltage	460
Primary Max Current	94.1A
Primary Markings	H0-H1
Primary Terminals	#2/0-6 AWG
Secondary Voltage	230
Secondary Max Current	188.3A
Secondary Markings	<u>X0-X1</u>
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 460 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	<u>Canada/RPM</u>
----------------------	-------------------