


OFFICIAL QUOTE

MP3C30H-M






MP3C30H-M


\$10,521.95 USD

SKU: f4be450f1796

Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE

MP3C30H-M



PRODUCT SPECIFICATIONS

Weight	710 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BR
kVA	30
Connection	MPC3P-5t
Incoming Voltage	480
Primary Breaker	<u>80A</u>
Interruping Rating	14kAIC @ 480V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	100A
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
Insuation Class	200°C
Panel Board	Push-On
Load Center Bus Material	Aluminum
# of Circuits	27
Impedance	1.5 - 3.0%
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-3
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered