

OFFICIAL QUOTE

BA112J-M/Z3






BA112J-M/Z3


\$10,220.00 CAD

SKU: 3d7399ae04a9

Categories: <u>Isolation Transformers</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 1030 lbs |
|-----------------|--------------|
| Phases | 3 |
| kVA | 112.5 |
| Connection | 3Ph-DY-5T-SD |
| Primary Voltage | 600 |



OFFICIAL QUOTE

BA112J-M/Z3



| Primary Max Current | <u>108.3A</u> |
|----------------------------|--|
| Primary Markings | H1-H2-H3 |
| Primary Terminals | 300MCM-6 |
| Secondary Voltage | <u>208Y/120</u> |
| Secondary Max Current | <u>312.3A</u> |
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | 300MCM-6 (2/Ph) |
| Primary Taps | +/- 2 x 2.5% |
| Conductor Material | <u>Aluminum</u> |
| Insuation Class | 220°C |
| BIL (Insulation) Level | <u>10kV</u> |
| Impedance | 4.0 - 6.0% |
| Sound (db) | 50 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | <u>E3R-8</u> |
| Finish | Polyster Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Efficiency | 98.74% |