





CS250J-Z \$193.00 CAD

SKU: ed2c3beff6e5 Categories: Control Transformers

PRODUCT SPECIFICATIONS

| Weight | 10 lbs |
|-----------------------|---------------------|
| Phases | 1 |
| VA | <u>250</u> |
| Connection | <u>1Ph-CT-SD-SD</u> |
| Primary Voltage | <u>600</u> |
| Primary Max Current | <u>0.42A</u> |
| Primary Markings | <u>H1-H2</u> |
| Primary Terminals | Terminals |
| Secondary Voltage | <u>12/24</u> |
| Secondary Max Current | <u>20.83A</u> |



CS250J-Z



| Secondary Markings | <u>X1-X2-X3-X4</u> |
|----------------------------|---|
| Secondary Terminals | Terminals |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Temperatue Rise | 80°C |
| Insuation Class | <u>130°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | N/A |
| Impedance | <u>5.0 - 7.0%</u> |
| Sound (db) | 40 |
| Enclosure Type | Core & Coil |
| Enclosure | See Chart |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered |
| Finish | N/AN/A |