



CS250J-Z

\$193.00 CAD

SKU: ed2c3beff6e5

Categories: [Control Transformers](#)

PRODUCT SPECIFICATIONS

| | |
|-----------------------|------------------------------|
| Weight | 10 lbs |
| Phases | 1 |
| VA | 250 |
| Connection | 1Ph-CT-SD-SD |
| Primary Voltage | 600 |
| Primary Max Current | 0.42A |
| Primary Markings | H1-H2 |
| Primary Terminals | Terminals |
| Secondary Voltage | 12/24 |
| Secondary Max Current | 20.83A |



| | |
|---------------------------------------|------------------------------------------------------------------------------------------------------|
| Secondary Markings | X1-X2-X3-X4 |
| Secondary Terminals | Terminals |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Temperatue Rise | 80°C |
| Insuation Class | 130°C |
| BIL (Insulation) Level | 10kV |
| Efficiency | N/A |
| Impedance | 5.0 – 7.0% |
| Sound (db) | 40 |
| Enclosure Type | Core & Coil |
| Enclosure | See Chart |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered |
| Finish | N/AN/A |