



## CS250J-Z

**\$142.14 USD**

SKU: ed2c3beff6e5

Categories: [Control Transformers](#)

### PRODUCT SPECIFICATIONS

|                       |                              |
|-----------------------|------------------------------|
| Weight                | 10 lbs                       |
| Phases                | <a href="#">1</a>            |
| VA                    | <a href="#">250</a>          |
| Connection            | <a href="#">1Ph-CT-SD-SD</a> |
| Primary Voltage       | <a href="#">600</a>          |
| Primary Max Current   | <a href="#">0.42A</a>        |
| Primary Markings      | <a href="#">H1-H2</a>        |
| Primary Terminals     | <a href="#">Terminals</a>    |
| Secondary Voltage     | <a href="#">12/24</a>        |
| Secondary Max Current | <a href="#">20.83A</a>       |



|                                       |  |
|---------------------------------------|--|
| <b>Secondary Markings</b>             | <a href="#">X1-X2-X3-X4</a>  |
| <b>Secondary Terminals</b>            | <a href="#">Terminals</a>  |
| <b>Primary Taps</b>                   | <a href="#">N/A</a>  |
| <b>Conductor Material</b>             | <a href="#">Copper</a>   |
| <b>Temperatue Rise</b>                | <a href="#">80°C</a>   |
| <b>Insuation Class</b>                | <a href="#">130°C</a>  |
| <b>BIL (Insulation) Level</b>         | <a href="#">10kV</a>   |
| <b>Efficiency</b>                     | <a href="#">N/A</a>  |
| <b>Impedance</b>                      | <a href="#">5.0 – 7.0%</a>   |
| <b>Sound (db)</b>                     | <a href="#">40</a>   |
| <b>Enclosure Type</b>                 | <a href="#">Core &amp; Coil</a>  |
| <b>Enclosure</b>                      | <a href="#">See Chart</a>  |
| <b>Standards &amp; Certifications</b> | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a> |
| <b>Finish</b>                         | <a href="#">N/AN/A</a>   |