



75KVA 400 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,213.90 CAD

Three Phase Autotransformer with a capacity of 75kVA, transforming 400Y Volts to 440Y Volts

SKU: RC75G1-H2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 75kVA, transforming 400Y Volts to 440Y Volts



PRODUCT SPECIFICATIONS

Weight	50 lbs
Phases	3
kVA	75
Connection	3PhA-NT-1
Primary Voltage	400
Primary Max Current	108.3A
Primary Markings	X1-X2-X3
Primary Terminals	#2/0-6 AWG
Secondary Voltage	440
Secondary Max Current	98.4A
Secondary Markings	H1-H2-H3
Secondary Terminals	#2/0-6 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

75KVA 400 VOLTS TO 440 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------