


OFFICIAL QUOTE

45KVA 277 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





45KVA 277 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

\$4,043.70 CAD

Three Phase Autotransformer with a capacity of 45kVA, transforming 277Y Volts to 115Y Volts

SKU: RC45D-A1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 45kVA, transforming 277Y Volts to 115Y Volts



OFFICIAL QUOTE



45KVA 277 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	193 lbs
Phases	<u>3</u>
kVA	45
Connection	<u>3PhA-NT-1</u>
Primary Voltage	277
Primary Max Current	93.8A
Primary Markings	H1-H2-H3
Primary Terminals	#2/0-6 AWG
Secondary Voltage	<u>115</u>
Secondary Max Current	225.9A
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	<u>E3R-6</u>
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

45KVA 277 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------