



**RS150H**

**\$1,788.89 USD**

SKU: c95465136802

Categories: [Motor Starters](#)

#### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



#### PRODUCT SPECIFICATIONS

|                     |                             |
|---------------------|-----------------------------|
| Weight              | 190 lbs                     |
| Phases              | <a href="#">3</a>           |
| HP                  | <a href="#">150</a>         |
| Connection          | <a href="#">3PhA-ST-0-3</a> |
| Primary Voltage     | <a href="#">480</a>         |
| Primary Max Current | <a href="#">180.4A</a>      |



|                            |  |
|----------------------------|--|
| Primary Markings           | <a href="#">H1-H2-H3</a>   |
| Primary Terminals          | <a href="#">Pads</a>   |
| Secondary Voltage          | <a href="#">50/65/80/100%</a>  |
| Secondary Max Current      | <a href="#">1732.1A</a>  |
| Secondary Markings         | <a href="#">A-B-C-D</a>  |
| Secondary Terminals        | <a href="#">Pads</a>   |
| Primary Taps               | <a href="#">N/A</a>  |
| Conductor Material         | <a href="#">Copper</a>   |
| Temperatue Rise            | <a href="#">150°C</a>  |
| Insuation Class            | <a href="#">220°C</a>  |
| BIL (Insulation) Level     | <a href="#">10kV</a>   |
| Efficiency                 | <a href="#">N/A</a>  |
| Impedance                  | <a href="#">N/A</a>  |
| Sound (db)                 | <a href="#">N/A</a>  |
| Enclosure Type             | <a href="#">Core &amp; Coil</a>  |
| Enclosure                  | <a href="#">N/A</a>  |
| Finish                     | <a href="#">N/A</a>  |
| Standards & Certifications | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |