


OFFICIAL QUOTE

15KVA 550 VOLTS TO 120 VOLTS SINGLE PHASE AUTOTRANSFORMER





15KVA 550 VOLTS TO 120 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$2,262.60 CAD


Single Phase Autotransformer with a capacity of 15kVA, transforming 550 Volts to 120 Volts

SKU: MC15J2-A

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 15kVA, transforming 550 Volts to 120 Volts



OFFICIAL QUOTE



15KVA 550 VOLTS TO 120 VOLTS SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 132.4 lbs |
| Phases | 1 |
| kVA | <u>15</u> |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | <u>550</u> |
| Primary Max Current | 15.7A |
| Primary Markings | H0-H1 |
| Primary Terminals | Terminal Blocks |
| Secondary Voltage | 120 |
| Secondary Max Current | 72.2A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | #2-14 AWG |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>2.5 – 4.5%</u> |
| Sound (db) | 45 dB |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-4</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

15KVA 550 VOLTS TO 120 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|