




BC9Q-M

\$2,090.00 CAD

SKU: ea0403c52095

Categories: [Isolation Transformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



PRODUCT SPECIFICATIONS

| | |
|----------------------------|------------------------------|
| Weight | 130 lbs |
| Phases | 3 |
| kVA | 9 |
| Connection | 3Ph-YY-3T-SD |
| Primary Voltage | 600Y/347 |
| Primary Max Current | 8.7A |



| | |
|---------------------------------------|--|
| Primary Markings | H0-H1-H2-H3 |
| Primary Terminals | Terminal Blocks |
| Secondary Voltage | 208Y/120 |
| Secondary Max Current | 25A |
| Secondary Markings | X0-X1-X2-X3 |
| Secondary Terminals | Terminal Blocks |
| Primary Taps | +/- 1 x 5% |
| Conductor Material | Copper |
| Insulation Class | 220°C |
| BIL (Insulation) Level | 10kV |
| Impedance | 5.0 – 6.5% |
| Sound (db) | 40 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-4 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |
| Efficiency | N/A |