



OFFICIAL QUOTE

100KVA 200 VOLTS TO 347 VOLTS SINGLE PHASE AUTOTRANSFORMER



100KVA 200 VOLTS TO 347 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$5,582.60 CAD

Single Phase Autotransformer with a capacity of
100kVA, transforming 200 Volts to 347 Volts

SKU: MC100B1-E

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 100kVA, transforming 200 Volts to 347 Volts



OFFICIAL QUOTE

100KVA 200 VOLTS TO 347 VOLTS
SINGLE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

Weight	363.6 lbs
Phases	1
kVA	100
Connection	1PhA-NT-1
Primary Voltage	200
Primary Max Current	288.7A
Primary Markings	X0-X1
Primary Terminals	Pads
Secondary Voltage	347
Secondary Max Current	166.4A
Secondary Markings	H0-H1
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

100KVA 200 VOLTS TO 347 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)