




100KVA 208 VOLTS TO 200 VOLTS SINGLE PHASE AUTOTRANSFORMER



\$1,273.50 CAD

Single Phase Autotransformer with a capacity of 100kVA, transforming 208 Volts to 200 Volts

SKU: MC100B-B1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 100kVA, transforming 208 Volts to 200 Volts



PRODUCT SPECIFICATIONS

Weight	88.9 lbs
Phases	1
kVA	100
Connection	1PhA-NT-1
Primary Voltage	208
Primary Max Current	277.6A
Primary Markings	H0-H1
Primary Terminals	Pads
Secondary Voltage	200
Secondary Max Current	288.7A
Secondary Markings	X0-X1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

100KVA 208 VOLTS TO 200 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------