



**100KVA 440 VOLTS TO 416 VOLTS
SINGLE PHASE AUTOTRANSFORMER**


**100KVA 440 VOLTS TO 416
VOLTS SINGLE PHASE
AUTOTRANSFORMER**

\$1,511.60 CAD



Single Phase Autotransformer with a capacity of 100kVA, transforming 440 Volts to 416 Volts

SKU: MC100H2-G

Categories: [Autotransformers](#)



SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 100kVA, transforming 440 Volts to 416 Volts



PRODUCT SPECIFICATIONS

Weight	100.4 lbs
Phases	1
kVA	100
Connection	1PhA-NT-1
Primary Voltage	440
Primary Max Current	131.2A
Primary Markings	H0-H1
Primary Terminals	300MCM-6
Secondary Voltage	416
Secondary Max Current	138.8A
Secondary Markings	X0-X1
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

100KVA 440 VOLTS TO 416 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)