



Diagram illustrating a 1D chain structure with three sites labeled $H0/X0$, $X1$, and $H1$. The sites are connected by a series of horizontal lines, with the middle site $X1$ having a vertical line extending downwards.

Page: 1



PRODUCT SPECIFICATIONS

Weight	82.1 lbs
Phases	1
kVA	10
Connection	1PhA-NT-1
Primary Voltage	240
Primary Max Current	24.1A
Primary Markings	X0-X1
Primary Terminals	Terminal Blocks
Secondary Voltage	460
Secondary Max Current	12.6A
Secondary Markings	H0-H1
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	40 dB
Enclosure Type	NEMA 1
Enclosure Size	E1-2
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
10KVA 240 VOLTS TO 460 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------