


OFFICIAL QUOTE

112KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





112KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER


\$6,910.60 CAD


Three Phase Autotransformer with a capacity of 112.5kVA, transforming 208Y Volts to 115Y Volts

SKU: RC112B-A1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 112.5kVA, transforming 208Y Volts to 115Y Volts



OFFICIAL QUOTE



112KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	404 lbs
Phases	<u>3</u>
kVA	112.5
Connection	<u>3PhA-NT-1</u>
Primary Voltage	208
Primary Max Current	312.3A
Primary Markings	H1-H2-H3
Primary Terminals	<u>Pads</u>
Secondary Voltage	115
Secondary Max Current	<u>564.8A</u>
Secondary Markings	<u>X1-X2-X3</u>
Secondary Terminals	<u>Pads</u>
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 - 3.5%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

112KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	------------