



OFFICIAL QUOTE

112KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



112KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,117.30 CAD

Three Phase Autotransformer with a capacity of
112.5kVA, transforming 440Y Volts to 415Y Volts

SKU: RC112H2-G2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 112.5kVA, transforming 440Y Volts to 415Y Volts



OFFICIAL QUOTE

112KVA 440 VOLTS TO 415 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	45 lbs
Phases	3
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	440
Primary Max Current	147.6A
Primary Markings	H1-H2-H3
Primary Terminals	300MCM-6
Secondary Voltage	415
Secondary Max Current	156.5A
Secondary Markings	X1-X2-X3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

112KVA 440 VOLTS TO 415 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)