



112KVA 550 VOLTS TO 200 VOLTS THREE PHASE AUTOTRANSFORMER

\$9,835.60 CAD

Three Phase Autotransformer with a capacity of 112.5kVA, transforming 550Y Volts to 200Y Volts

SKU: RC112J2-B1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 112.5kVA, transforming 550Y Volts to 200Y Volts



PRODUCT SPECIFICATIONS

Weight	606 lbs
Phases	3
kVA	112.5
Connection	3PhA-NT-1
Primary Voltage	550
Primary Max Current	118.1A
Primary Markings	H1-H2-H3
Primary Terminals	300MCM-6
Secondary Voltage	200
Secondary Max Current	324.8A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

112KVA 550 VOLTS TO 200 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------