1500KVA 440 VOLTS TO 220 VOLTS THREE PHASE AUTOTRANSFORMER

$93,841.30 CAD

Three Phase Autotransformer with a capacity of 1500kVA, transforming 440Y Volts to 220Y Volts

SKU: RC1500H2-C2
Categories: Autotransformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES

Three Phase Autotransformer with a capacity of 1500kVA, transforming 440Y Volts to 220Y Volts

PRODUCT SPECIFICATIONS

Weight	5830 lbs
Phases	3
kVA	1500
Connection	3PhA-NT-1
Primary Voltage	440
Primary Max Current	1968.2A
Primary Markings	H1-H2-H3
Primary Terminals	Pads
Secondary Voltage	220
Secondary Max Current	3936.5A
Secondary Markings	X1-X2-X3
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	64
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-11
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered

Country/Manufacturer	Canada/RPM