



150KVA 115 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER

\$9,091.80 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 115Y Volts to 575Y Volts

SKU: RA150A1-J1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 150kVA, transforming 115Y Volts to 575Y Volts



PRODUCT SPECIFICATIONS

Weight	828 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	115
Primary Max Current	753.1A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	575
Secondary Max Current	150.6A
Secondary Markings	H1-H2-H3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 115 VOLTS TO 575 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------