




**150KVA 208 VOLTS TO 440 VOLTS
THREE PHASE AUTOTRANSFORMER**



150KVA 208 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



\$9,744.00 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 208Y Volts to 440Y Volts

SKU: RC150B-H2

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 150kVA, transforming 208Y Volts to 440Y Volts



PRODUCT SPECIFICATIONS

Weight	684 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	208
Primary Max Current	416.4A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	440
Secondary Max Current	196.8A
Secondary Markings	H1-H2-H3
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 208 VOLTS TO 440 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------