



150KVA 415 VOLTS TO 480 VOLTS THREE PHASE AUTOTRANSFORMER

\$3,000.60 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 415Y Volts to 480Y Volts

SKU: RA150G2-H

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 150kVA, transforming 415Y Volts to 480Y Volts



PRODUCT SPECIFICATIONS

Weight	130 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	415
Primary Max Current	208.7A
Primary Markings	X1-X2-X3
Primary Terminals	600MCM-2
Secondary Voltage	480
Secondary Max Current	180.4A
Secondary Markings	H1-H2-H3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-5
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 415 VOLTS TO 480 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------