OFFICIAL QUOTE

150KVA 415 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER



150KVA 415 VOLTS TO 550 VOLTS THREE PHASE AUTOTRANSFORMER

$4,898.40 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 415Y Volts to 550Y Volts

SKU: RC150G2-J2
Categories: Autotransformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 415Y Volts to 550Y Volts

PRODUCT SPECIFICATIONS

Weight	284 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	415
Primary Max Current	208.7A
Primary Markings	X1-X2-X3
Primary Terminals	600MCM-2
Secondary Voltage	550
Secondary Max Current	157.5A
Secondary Markings	H1-H2-H3
Secondary Terminals	300MCM-6
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.0 – 3.0%
Sound (db)	45
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered

Country/Manufacturer	Canada/RPM