



150KVA 440 VOLTS TO 230 VOLTS SINGLE PHASE AUTOTRANSFORMER


\$8,257.00 CAD

Single Phase Autotransformer with a capacity of 150kVA, transforming 440 Volts to 230 Volts

SKU: MC150H2-C1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 150kVA, transforming 440 Volts to 230 Volts



PRODUCT SPECIFICATIONS

Weight	579.5 lbs
Phases	1
kVA	150
Connection	1PhA-NT-1
Primary Voltage	440
Primary Max Current	196.8A
Primary Markings	H0-H1
Primary Terminals	600MCM-2
Secondary Voltage	230
Secondary Max Current	376.5A
Secondary Markings	X0-X1
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	55 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-7
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 440 VOLTS TO 230 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------