




150KVA 575 VOLTS TO 460 VOLTS SINGLE PHASE AUTOTRANSFORMER



\$4,218.50 CAD

Single Phase Autotransformer with a capacity of 150kVA, transforming 575 Volts to 460 Volts

SKU: MC150J1-H1

Categories: [Autotransformers](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Autotransformer with a capacity of 150kVA, transforming 575 Volts to 460 Volts



PRODUCT SPECIFICATIONS

Weight	282.9 lbs
Phases	1
kVA	150
Connection	1PhA-NT-1
Primary Voltage	575
Primary Max Current	150.6A
Primary Markings	H0-H1
Primary Terminals	300MCM-6
Secondary Voltage	460
Secondary Max Current	188.3A
Secondary Markings	X0-X1
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	0.5 – 1.5%
Sound (db)	45 dB
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-6
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE

150KVA 575 VOLTS TO 460 VOLTS
SINGLE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------