

OFFICIAL QUOTE

15KVA 220 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER





15KVA 220 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER

\$2,358.80 CAD

Three Phase Autotransformer with a capacity of 15kVA, transforming 220Y Volts to 440Y Volts

SKU: RC15C2-H2 Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 15kVA, transforming 220Y Volts to 440Y Volts



OFFICIAL QUOTE

15KVA 220 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

Weight	55 lbs
Phases	3
kVA	<u>15</u>
Connection	<u>3PhA-NT-1</u>
Primary Voltage	220
Primary Max Current	<u>39.4A</u>
Primary Markings	<u>X1-X2-X3</u>
Primary Terminals	<u>#2-14 AWG</u>
Secondary Voltage	<u>440</u>
Secondary Max Current	<u>19.7A</u>
Secondary Markings	<u>H1-H2-H3</u>
Secondary Terminals	Terminal Blocks
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Insulation Class	<u>220°C (Class H)</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	<u>N/A</u>
Impedance Range	<u>1.5 – 3.5%</u>
Sound (db)	<u>40</u>
Enclosure Type	NEMA 1
Enclosure Size	<u>E1-3</u>
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	<u>CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015</u> <u>Registered</u>



OFFICIAL QUOTE

15KVA 220 VOLTS TO 440 VOLTS THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

Canada/RPM